

# GAS DETECTORS

## SOLO GAS DETECTORS

- Easy-to-service, single-gas detector
- Lightweight convenience
- High standards of sensor quality and reliability
- Compatible with IntelliDoX
- Bump testing (qualitative function check) of the sensors, is a recommended function and requires test gas cylinders and bump test accessories
- Provides real-time visibility into the status and safety of hazardous-area workers
- Connected Bluetooth low energy (BLE) capabilities
- Wireless feature allows access from any device with an internet connection to get remote visibility on worker safety and location



HZ329

## Honeywell

| Yellow Model No. | Mfg. No.  | Black Model No. | Mfg. No.  | Hazard                     | Measuring Range   | Price /Each |
|------------------|-----------|-----------------|-----------|----------------------------|-------------------|-------------|
| HZ363            | BWS1-C-Y  | HZ380           | BWS1-C-B  | Cl <sub>2</sub>            | 0 ppm to 100 ppm  |             |
| HZ364            | BWS1-V-Y  | HZ381           | BWS1-V-B  | ClO <sub>2</sub>           | 0 ppm to 100 ppm  |             |
| HZ365            | BWS1-ML-Y | HZ382           | BWS1-ML-B | CO                         | 0 ppm to 2000 ppm |             |
| HZ366            | BWS1-M2-Y | HZ383           | BWS1-M2-B | CO                         | 0 ppm to 2000 ppm |             |
| HZ367            | BWS1-E-Y  | HZ384           | BWS1-E-B  | ETO                        | 0 ppm to 50 ppm   |             |
| HZ368            | BWS1-R-Y  | HZ385           | BWS1-R-B  | H <sub>2</sub>             | 0 ppm to 1 ppm    |             |
| HZ369            | BWS1-HL-Y | HZ386           | BWS1-HL-B | H <sub>2</sub> S           | 0 ppm to 100 ppm  |             |
| HZ370            | BWS1-H2-Y | HZ387           | BWS1-H2-B | H <sub>2</sub> S ext range | 0 ppm to 1000 ppm |             |
| HZ371            | BWS1-Z-Y  | HZ388           | BWS1-Z-B  | HCN                        | 0 ppm to 100 ppm  |             |
| HZ372            | BWS1-A-Y  | HZ389           | BWS1-A-B  | NH <sub>3</sub>            | 0 ppm to 200 ppm  |             |
| HZ373            | BWS1-A2-Y | HZ390           | BWS1-A2-B | NH <sub>3</sub> ext range  | 0 ppm to 500 ppm  |             |
| HZ374            | BWS1-N-Y  | HZ391           | BWS1-N-B  | Nitric Oxide               | 0 ppm to 250 ppm  |             |
| HZ375            | BWS1-D-Y  | HZ392           | BWS1-D-B  | NO <sub>2</sub>            | 0 ppm to 100 ppm  |             |
| HZ376            | BWS1-XL-Y | HZ393           | BWS1-XL-B | O <sub>2</sub>             | 0 v/v to 0.3 v/v  |             |
| HZ377            | BWS1-G-Y  | HZ394           | BWS1-G-B  | O <sub>2</sub>             | 0 ppm to 1 ppm    |             |
| HZ378            | BWS1-P-Y  | HZ395           | BWS1-P-B  | PH <sub>3</sub>            | 0 ppm to 5 ppm    |             |
| HZ379            | BWS1-S-Y  | HZ396           | BWS1-S-B  | SO <sub>2</sub>            | 0 ppm to 100 ppm  |             |

## INTELLIDOX DOCKING STATIONS

- The IntelliDoX system is expandable to five docking modules helping you drive productivity, reliability and efficiency
- Provides a new level of customization for bump testing, configuration and record-keeping in a maintenance-free detector
- Configure alarm set points and change detector settings throughout the operation life of the BW Clip
- Quick and easy setup — great for turnarounds
- Each module has its own easy-to-read LCD screen and keypad for independent operation



HZ402

## Honeywell

| Model No. | Mfg. No. | Compatible with                | Price/Each |
|-----------|----------|--------------------------------|------------|
| HZ187     | DX-CLIP  | BW Clip                        |            |
| HZ286     | DX-MCLP  | BW MicroClip XL / MicroClip X3 |            |
| HZ402     | DX-SOLO  | BW Solo                        |            |
| HZ404     | DX-ULTRA | BW Ultra                       |            |

### ACCESSORIES

| Model  | Mfg. No    | Description                    | Price/Each |
|--------|------------|--------------------------------|------------|
| HZ188* | DX-ENBL-NA | Enabler Kit                    |            |
| HZ190  | DX-MI-KEY  | Multi-Inlet Key, For Solo only |            |

\* Enabler Kit includes power supply with region-specific AC power cord, ethernet cable, inlet (purge) filter assembly, 3 ft. / 1 m calibration gas tubing, 3 ft. / 1 m purge gas tubing, 15 ft. / 4.5 m exhaust tubing, quick connect fittings and IntelliDoX inlet end plate.

## FIVE UNIT CRADLE CHARGER FOR GASALERTMAX XT II MULTI-GAS DETECTORS

Model No. HX926  
Mfg. No. XT-C01-MC5  
Price/Each \$



## Honeywell

**AURORA**  
TOOLS

Celebrating **15** YEARS

**EXCEEDING EXPECTATIONS**

